QUICK REFERENCE SETBACK REQUIREMENTS BY DISTRICT

	<u> </u>	T		*Yard Setbacks				
District	Minimum Building Area (square ft.)	Minimum Lot Area (square ft.)	Minimum Lot Width	Minimum Front Yard	Minimum Side Yard (per side)	Minimum Rear Yard	Maximum Building Height	Maximum Percent Lot Coverage
S-1 Special		125,000	300'	60'	50'	60'	45' Principal	20%
R-1 Low Density Residential	1,500	10,000	90'	30'	10'	25'	35' Principal 15' Access.	35%
R-2 Medium Density Residential Zero Lot Line	1,200	8,000 single 10,000 two-family	90' 100' for 2 family dwellng unit	30'	10'	25'	35' Principal 15' Access.	40%
R-3 High Density Residential	750	6,000 Single 8,000 2-Fam 3,000/unit for Multi-Fam. 20,000 Other	60' Single 80' 2-Fam. 100' Multi-Family & Other	30'	10'	25'	45' Principal 15' Access.	40%
R-O Residence & Office	1,000 per unit	12,000 Res. 16,000 Other	100' Res. 100' Other	40'	15' 10' Access.	25' 10' Access.	45' Principal	70%
B-1 General Business		20,000	100'	40'	15' 10' Access.	25' 10' Access.	45' Principal 45' Access.	40%
B-2 Central Business		None	None	None	None	None 20' if abutting Res. Dist.	72' Principal 25' Access.	100% Unless adjacent to Res. Dist.
B-3 Community Shopping Center		200,000 Prime Dev. 20,000 Outlots	400' Prime	60'	30' 20' Access.	40' 20' Access.	35' Principal 35' Access.	30%
M Manufacturing		45,000	200'	50'	30'	40' 10' Access.	45' Principal 45' Access.	50%
PUD	See Chapter 20 for requirements							

^{*} SETBACK - is from the Right-of-Way in the front yard and from the property line from the rear and side yards